



US008869839B1

(12) **United States Patent**  
**D'Hulster**

(10) **Patent No.:** **US 8,869,839 B1**  
(45) **Date of Patent:** **Oct. 28, 2014**

(54) **METHOD AND DEVICE FOR REPAIRING PIPING**

(75) Inventor: **Gerald Scott D'Hulster**, Clearwater, FL (US)

(73) Assignee: **Perma-Liner Industries, LLC**, Clearwater, FL (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 1090 days.

(21) Appl. No.: **12/731,471**

(22) Filed: **Mar. 25, 2010**

(51) **Int. Cl.**  
**F16L 55/16** (2006.01)

(52) **U.S. Cl.**  
USPC ..... **138/98**; 138/97; 405/150.1; 405/184.2

(58) **Field of Classification Search**  
USPC ..... 138/97, 98; 405/150.1, 184.2  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,009,063	A	2/1977	Wood	
4,064,211	A	12/1977	Wood	
4,366,012	A	12/1982	Wood	
5,598,873	A *	2/1997	Kamiyama et al.	138/98
5,609,439	A *	3/1997	Schreiner et al.	405/184.2
5,765,597	A *	6/1998	Kiest et al.	138/98
5,927,341	A	7/1999	Taylor	
5,950,682	A *	9/1999	Kiest, Jr.	138/98

6,001,212	A *	12/1999	Polivka et al.	156/287
6,039,079	A	3/2000	Kiest, Jr.	
6,337,114	B1 *	1/2002	Wood et al.	428/36.9
6,482,280	B1 *	11/2002	Kiest et al.	156/87
6,899,832	B2 *	5/2005	Wood	264/36.17
7,216,674	B2	5/2007	Manners	
7,845,372	B2 *	12/2010	Kiest, Jr.	138/98
7,987,873	B2 *	8/2011	Kiest, Jr.	138/98
2005/0211372	A1 *	9/2005	Wood	156/287
2006/0243337	A1	11/2006	Manners	
2007/0001330	A1 *	1/2007	Driver et al.	264/36.17
2007/0261751	A1 *	11/2007	Lepola	138/98
2008/0245433	A1 *	10/2008	Warren	138/98
2009/0056823	A1 *	3/2009	Kiest, Jr.	138/98
2013/0139922	A1 *	6/2013	D'Hulster et al.	138/93

\* cited by examiner

Primary Examiner — James Hook

(74) *Attorney, Agent, or Firm* — McKee, Voorhees & Sease

(57) **ABSTRACT**

An device and method for repairing the junction of a main pipe line and a lateral pipe. The device uses a series of independently controlled bladders to adjust the timing and pressure exerted by the bladders on the pipes. The device also uses a liner assembly of resin absorbent material is formed, with a tubular lateral liner connected to a concentric circular main liner. The liner also includes an opening to facilitate loading of the liner in the device. Upon loading the bladders and resin-embedded liner into a train, the device is positioned and the bladders independently inflated, either concurrently or in sequence, installing the liner assembly onto the pipe. Once the resin is cured, the bladder assembly and launcher are removed from the sewer pipe.

**14 Claims, 7 Drawing Sheets**

