

(12) STANDARD PATENT
(19) AUSTRALIAN PATENT OFFICE

(11) Application No. **AU 2013222067 B2**

(54) Title
Apparatus and method for repairing pipes

(51) International Patent Classification(s)
F16L 55/162 (2006.01)

(21) Application No: **2013222067** (22) Date of Filing: **2013.02.26**

(87) WIPO No: **WO13/126925**

(30) Priority Data

(31) Number	(32) Date	(33) Country
61/603,360	2012.02.26	US

(43) Publication Date: **2013.08.29**

(44) Accepted Journal Date: **2016.02.18**

(71) Applicant(s)
Perma-Liner Industries, LLC

(72) Inventor(s)
D'Hulster, Gerald

(74) Agent / Attorney
Davies Collison Cave, Level 15 1 Nicholson Street, MELBOURNE, VIC, 3000

(56) Related Art
US 2010/0154187 A1
US 2008/0047624 A1
WO 2012/016244 A2
GB 989847 A




- (51) International Patent Classification:
F16L 55/162 (2006.01)
- (21) International Application Number:
PCT/US2013/027791
- (22) International Filing Date:
26 February 2013 (26.02.2013)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
61/603,360 26 February 2012 (26.02.2012) US
- (71) Applicant: PERMA-LINER INDUSTRIES, LLC
[US/US]; 13000 Automobile Blvd., Suite 300, Clearwater,
Florida 33762 (US).
- (72) Inventor; and
(71) Applicant : D'HULSTER, Gerald [US/US]; 13000
Automobile Blvd., Suite 300, Clearwater, Florida 33762
(US).
- (74) Agent: MOHRHAUSER, Luke T.; McKee, Voorhees &
Sease, P.L.C., 801 Grand Avenue, Suite 3200, Des Moines,
Iowa 50309-2721 (US).

- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


Published:

— with international search report (Art. 21(3))

(54) Title: APPARATUS AND METHOD FOR REPAIRING PIPES



(57) Abstract: An apparatus and method that accelerates curing of resin in a liner for a buried pipe includes an air inversion unit connected to an air compressor. The apparatus includes an inversion head with an interior inflatable plug. The plug, when inflated, creates a substantially airtight seal thereby maintaining pressure within the liner tube. The inversion head can then be removed from the liner inversion apparatus and a curing cap can be installed. To improve the wetting process, a vacuum head is installed at the inversion head and connected to a vacuum source. One end of the liner tube is attached to the inversion head and curable resin is poured into the opposite end. Vacuum pressure is applied to assist in the movement of the resin through the liner tube, ensuring uniform saturation. The resin is mechanically manipulated through the liner tube as the vacuum pressure is applied.



2013222067 21 Jan 2016

APPARATUS AND METHOD FOR REPAIRING PIPES

This application claims priority under 35 U.S.C. § 119 to provisional application Serial No. 61/603,360, filed February 26, 2012, which is herein incorporated by reference
5 in its entirety.

The present invention relates generally to liners that are used to repair buried pipes without excavation. More particularly, but not exclusively, it relates to an apparatus and method that reduces the amount of time required to complete such repairs.

Methods of rehabilitating damaged pipes by inverting a tubular liner impregnated
10 with curable resin are known. The known methods of installing a liner to repair a buried pipe, while it remains underground, involve inserting a liner into the pipe and forcing the liner into engagement with the inner walls of the pipe by inflating a bladder. The liner is impregnated with curable resins prior to insertion and the bladder must remain inflated until the resin cures. The time required for the resin to cure, however, ranges from three to
15 eight hours, depending upon ambient temperatures.

Thus, there is a need in the art for an apparatus and method that provides a shorter curing time regardless of ambient temperatures.

It is therefore a primary object, feature, and/or advantage of embodiments of the present invention to provide a method and system for identifying a product.

20 It is another object, feature, and/or advantage of embodiments of the present invention to provide an inversion head that can be attached to vacuums, fluid sources, and curing heads quickly and easily to repair a damaged section of pipe.

It is yet another object, feature, and/or advantage of embodiments of the present invention to provide an inflatable plug connected to an inversion head to plug an inflated
25 liner to allow a different attachment to be attached to the inversion head.

It is still another object, feature, and/or advantage of embodiments of the present invention to provide a vacuum source attached to the inversion head to aid in impregnating a liner with a material capable of curing and hardening.

30 These and/or other objects, features, and advantages of embodiments of the present invention will be apparent to those skilled in the art. The present invention is not to be limited to or by these objects, features and advantages. No single embodiment need provide each and every object, feature, or advantage.

2013222067 21 Jan 2016

The long-standing but heretofore unfulfilled need for an apparatus and method that shortens resin-curing times may be met by a new, useful, and non-obvious invention. The apparatus includes an inversion head with an interior inflatable bladder. The bladder, when inflated, creates a substantially airtight seal thereby maintaining pressure within the liner tube. The inversion head can then be removed from the liner inversion apparatus and a curing cap can be installed.

To improve the "wetting process," a vacuum head is installed in the inversion head and connected to a vacuum source. One end of the liner tube is attached to the inversion head and curable resin is poured into the opposite end. Vacuum pressure is applied to assist in the movement of the resin through the liner tube ensuring uniform saturation. The resin is preferable mechanically manipulated through the liner tube as the vacuum pressure is applied.

According to an aspect of the invention, there is provided a method of repairing a damaged section of a pipe, comprising: providing a liner having an open first end and a substantially closed second end; impregnating the liner with a material capable of curing and hardening; inverting the liner into the pipe with an inversion head, wherein the first end of the liner is attached to a portion of the inversion head; inflating the liner using a source of pressurized fluid to create pressure within the liner which presses the liner against the wall of the pipe; inflating a plug at least partially within the inversion head to substantially close the open end of the liner at the inversion head and maintain pressure within the liner; wherein the liner is inverted through the inversion head prior to the inflation of the plug; and allowing the material to cure and harden.

According to another aspect of the invention, there is provided an assembly for repairing a damaged section of a pipe, comprising: an inversion head having an intake end and an opposite discharge end; a liner having an open first end and a substantially closed second end, the first end attached to the discharge end of the inversion head; a plug positioned at least partially within the inversion head and configured to be inflated to substantially close off the open first end of the liner; wherein the intake end of the inversion head configured to removably attach to an inversion member for inflating the liner, and a curing head for curing a material capable of curing and hardening that is impregnated in the liner; and wherein the liner is inverted through the inversion head and the plug to be positioned within the damaged section of pipe.

2013222067 21 Jan 2016

According to yet another aspect of the invention, there is provided a method of repairing a damaged section of a pipe, comprising: providing a liner having an open first end and a substantially closed second end; attaching the open end of the liner to a discharge end of an inversion head; impregnating the liner with a material capable of curing and hardening by applying vacuum pressure at an intake end of the inversion head; 5 inverting the liner into the pipe by a fluid source attached to the intake end of the inversion head; inflating the liner using a source of pressurized fluid to create pressure within the liner which presses the liner against the wall of the pipe; inflating a plug at least partially within the inversion head to substantially close the open end of the liner at the inversion 10 head and maintain pressure within the liner; wherein the liner is inverted through the inversion head prior to the inflation of the plug; and allowing the material to cure and harden.

The present invention will now be described, by way of non-limiting example only, with reference to the accompanying drawings, in which:

15 Fig. 1 is a perspective view of an illustrative curing cap.

Fig. 2 is a side plan view of an illustrative curing cap.

Fig. 3A is a side plan view of an inversion head, with an un-inverted tubular liner positioned thereon.

20 Fig. 3B is a side plan view of an illustrative curing cap installed in an inversion head, which is in turn installed in the open end of an liner tube.

Fig. 4A is a side plan view of an illustrative curing cap installed in an inversion head with the flexible tube extending there through.

Fig. 4B is a side plan view of an illustrative curing cap installed in an inversion head with the flexible tube extending there through and into the lumen of the tubular liner.

25 Fig. 5 is a diagrammatic view of an illustrative manifold.

Fig. 6A is a diagrammatic view of an alternative inversion head.

Fig. 6B is a diagrammatic view of an alternative inversion head.

Fig. 7 is a diagrammatic view of a vacuum head installed in the intake of an inversion head.

30 While the present invention is shown for use with sewer pipeline repair, it should be appreciated that embodiments of the invention can be utilized for repairing other types of pipes, ducts, tunnels and shafts, such as gas, water, oil, steam and compressed air

2013222067 21 Jan 2016

conduits. Figs. 1 and 2 depict an illustrative embodiment of a curing cap or head, which is denoted as a whole by the reference numeral 10. The curing cap 10 includes a substantially circular body 12 having an outer side 12a and an inner side 12b. The outer side 12a further includes an inflation port 14, a curing port 16, and a discharge port 18. All ports are preferably arranged to provide unidirectional fluid communication between the outer side 12a and the inner side 12b of the circular body 12. The inner side 12b of the circular body 12 is received by an intake 22 of inversion head 20 (Fig. 3A). The discharge end 24 releasably engages the interior of the open end 26a of the liner tube 26.

Two types of liner tubes are commonly used. The first type of liner comprises a felt or fiberglass lining, having a substantially closed end and an opposite open end, and being impregnated with a curable resin. The second type includes a lining composition of two (2) main layers; a first layer comprising an inflatable bladder having a substantially closed end and an opposite open end, and a second layer of felt or fiberglass lining that is impregnated with a curable resin.

The liner tube 26 preferably comprises a resin-absorbent layer, such as a felt layer (26b), as well as a resin impervious layer (26c). The resin impervious layer may comprise a rubber, elastomer, or plastic, as is known in the art. The felt layer is adapted to absorb a resin or grout material, and the plastic layer is adapted to provide an impervious, smooth, and continuous surface. Prior to inverting the liner tube, the plastic layer is located on the outside of the liner tube and the felt layer is located on the inside. During the inversion process (described below), the liner tube 26 is inverted such that the felt layer is on the outside of the liner tube and the smooth plastic layer is on the inside of the liner tube. Use of an impermeable coating on the liner tube allows the liner tube to be inflated and inverted without the use of a separate bladder. However, embodiments of the invention also contemplate that a bladder can be used, which can negate the need for the impervious layer of the liner. In embodiments using an inflatable bladder, the bladder overlies the felt lining and can contact with plastic layer 26c. After inversion, the bladder will be generally within the liner, with the felt layer of the liner against the wall of the pipe.

Prior to inversion, the intake 22 of the inversion head 20 is connected (via a tubular conduit) to a liner dispensing unit (which normally include a source of pressurized air or other fluid). The dispensing unit holds a length of resin soaked liner prior to delivery.

During inversion, the air or other fluid under pressure flows through the system from the dispensing unit towards inversion head 20.

As shown in FIG. 3A, the open end 26a of the liner tube 26 is fitted over the discharge end 24 of the inversion head 20 and is secured in place to create an airtight connection therearound, ensuring the air under pressure causes the closed leading end of the liner tube 26 (not shown) to follow a path of travel through the curing cap 20 into the interior or lumen of the pipe, thereby inverting said liner as said closed end is propelled to the distal end of the pipe by said fluid under pressure (see FIG. 3B).

Accordingly, the liner tube 26 is fully inverted along its entire extent when the closed end of the liner tube 26 reaches the distal end of the pipe. The impervious layer now forms the interior surface of liner tube 26 and the resin-impregnated outer layer now forms the exterior layer, which is pressed against the inner sidewalls of the pipe by the pressure of said gaseous or liquid fluid.

Fluid, such as air or steam, from the inversion compressor further causes the liner 26 (or bladder/liner combination) to expand radially so that the resin-impregnated portion of the liner 26 comes into contact with the interior of the pipe to be repaired. Air pressure is continued against the interior of the liner (or inflatable bladder) to force the resin impregnated or coated surface of the liner 26 into contact with the interior of the pipe.

Once the liner tube 26 is fully inverted, the inversion head 20 is uncoupled from the dispensing unit and compressed air source. Turning now to Fig. 4A, a curing cap 10 is then coupled with the intake 22 of the inversion head 20 (FIG. 3B). An inflation port 14 is connected to an air compressor (not shown) via an airline 14a. Air from the compressor maintains the pressure within the liner 26 to keep the resin impregnated portion or layer (26b) of the liner 26 in contact with the interior of the pipe.

The curing port 16 is connected, via a flexible curing tube 16a, to a manifold 30 (see Fig. 5), which is in turn in fluid communication with a heated fluid source and an air compressor (not shown). In an alternative embodiment, however, it is possible to use a single air compressor connected to the manifold to provide connections to both the inflation port 14 and the curing port 16. The curing port 16 is preferably of a slip-ring configuration, but can be adapted for any configuration that allows the curing tube 16a to slide through the curing port 16, while maintaining a substantially fluid-tight seal.

The drainage port 18 is also connected to the manifold 30 and provides fluid communication, via a drainage line 18a, from the interior of the pipe outward to the manifold 30.

The manifold 30, Fig. 5, includes a heat inlet 32, an air inlet 34, and an outlet 36.

5 The heat inlet 32 is in fluid communication with a heating source, which provides heated fluid (i.e. hot water or steam) to the system. The flow of heated fluid into the system is controlled by a heat valve 32a, and the temperature and/or pressure of the heated fluid is monitored by a gauge 32b. The air inlet 34 is in fluid communication with a drainage air compressor, which provides air, under pressure, to the system. The flow of air under
10 pressure into the system is controlled by an air valve 34a, and the temperature and/or pressure of the air is monitored by a gauge 34b. As previously stated, the drainage air compressor can be replaced by the inversion air compressor using linkages as known in the art. Both the heat fluid inlet 32 and the air inlet 34 are in open fluid communication with the outlet valve 36. For example, when the heat valve 32a is open, heated fluid is permitted
15 to pass through the manifold 30, thereby exiting the outlet 36 and entering the system via the curing tube 16a.

The manifold 30 also includes a drainage inlet 38, connected to the drainage line 18, which further comprises a drainage valve 38a and a temperature/pressure gauge 38b. Fluids leaving the system via the drainage line 18a can be monitored via the gauge 38b and
20 disposed of when safe through the drainage outlet 38c.

Another aspect of the inventive method occurs after the liner tube 26 has been inverted and is being pressed against the sides of the pipe under pressure. This aspect includes the steps of inserting a curing tube 16a into the lumen of the liner tube 26, opening the heat valve 32 so that heated fluid flows through the manifold 30 via the outlet
25 36, into curing the curing tube 16a, and into the lumen of the liner tube 26.

The curing tube 16a is an elongate flexible tube including a substantially spherical guide 17 at its distal end. The curing tube 16a also includes a series of perforations 19 proximal to the spherical guide 17. Once the liner tube 26 is fully extended, the curing tube 16a is fed through the curing port 16, thereby advancing the guide 17 through the lumen of
30 the liner tube 26. The substantially spherical shape of the guide 17 allows the distal end of the tube to easily navigate corners and bends. Once properly positioned, the heated fluid passes through the curing tube 16a and out the perforations 19 into the lumen of the liner

tube 26 near its distal end. This ensures that the liner tube 26 is heated from the distal (closed) end toward the proximal (open) end.

As the heated fluid fills the lumen of the liner tube from the distal end, the air under pressure used to invert the liner tube is permitted to escape through the drainage port 18 and back towards the manifold 30 via the drainage line 18a. The gauge 38a is monitored as the fluids (air under pressure, steam or hot water) pass therethrough. When the gauge shows that the temperatures of the drainage fluids are substantially equal to the temperature of the heated fluid entering the system, this indicates that the heated fluid has reached the proximal end of the liner tube 26. It can now be assumed that the liner tube 16 is substantially filled with said heated fluid. The heat valve 32a and the drainage valve 38a can then be closed, fully or partially, so that the liner tube 26 is not over-pressurized. The resin cures within a significantly abbreviated time because the heat of the heated fluid is conducted by the inflatable bladder (or plastic liner layer 26c) into the resin-impregnated layer 26b, where it acts as a catalyst.

When the resin has sufficiently cured, the drainage valve 36a is opened to allow the lumen of the liner tube to be emptied of the added fluid. To facilitate drainage, the air valve 34a is opened, forcing air under pressure through the perforations 19 in the distal end of the curing tube 16a. This air under pressure forces any remaining heated fluid through the drainage port 18, through the line 18a and into the drainage inlet 38a. The inversion head 20 and curing cap 10 can be removed once substantially all heated fluids are removed from the lumen of the liner tube 26.

According to an aspect of the invention shown generally in Fig. 6A, the inversion head 20 can be adapted with an inflatable internal plug 29 disposed interiorly and connected to a source of pressurized fluid (preferably air). The plug 29 can be positioned within the inversion head 20 and can also be attached to a portion of the inversion head 20. After the liner tube 26 has been inverted and pressurized, the plug 29 is inflated, thereby forming a substantially airtight seal at the open end of the liner. Once the plug 29 is inflated, it is possible to remove the inversion head 20 from the liner-dispensing unit without maintaining pressure within the liner tube 26. The curing cap 10 (or other cap) can then be attached to the inversion head 20, as described above.

The plug 29 can be recessed within a groove in the interior wall of the inversion head 29. This arrangement permits the liner tube 26 to travel smoothly through the

2013222067 21 Jan 2016

inversion head as it is inverted. The plug 29 can be annular, but can be inflated to occlude the interior of inversion head 20, not unlike a balloon (Fig. 6B).

Alternatively, the plug 29 can be any mechanical means of occluding the interior of the inversion head 20 to provide a substantially airtight seal. Examples include an iris-like device, a ball valve, a check valve, a pipe interrupter, or the like.

Prior to use, the curable resin material is applied to the liner tube 26 during a "wetting out" process. The liner tube 26 is attached to the inversion head 20, with the felt or resin-absorbent layer on the interior. Resin is then poured into the opposite end of the liner tube 26. A roller is used over the liner to ensure that the resin is spread evenly along the length of the liner tube 26. An aspect of the invention improves on this method by the use of a vacuum head 100 attached to the inversion head 20, as is shown in Fig. 7. The vacuum head 100 can be attached at the intake 22 of the inversion head.

During the wetting or wetting out process, the vacuum head 100 is attached to the intake 22 of the inversion head 20. After the resin is poured into the liner tube 26 and after or while the roller is rolled over the liner, negative (vacuum) pressure is provided to the interior of the liner tube 26 via the vacuum head 100. The negative or vacuum pressure can be provided by a vacuum source (not shown). This can be any negative pressure source, such as a vacuum or the like. The addition of the vacuum source and pressure helps ensure the even spreading of the resin throughout the liner tube 26. Vacuum (negative) pressure can be used with or without the use of a roller, as well. Once the liner tube 26 is impregnated or saturated with resin, the vacuum head 100 can be removed from the intake 22 of the inversion head 20, and the fluid source and/or curing head can be attached, as described above.

All documents cited herein are incorporated herein by reference in their entirety. The invention is illustrated by the preceding embodiments. These embodiments are provided to aid in the understanding of the invention and are not to be construed as a limitation with regard to the arrangement of the parts shown in the figures or the order of steps provided.

It is intended that all matters contained in the foregoing disclosure or shown in the accompanying drawings shall be interpreted as illustrative and not in a limiting sense.

The foregoing description has been presented for purposes of illustration and description, and is not intended to be an exhaustive list or to limit the invention to precise

2013222067 21 Jan 2016

forms disclosed. It is contemplated that other alternative processes obvious to those skilled in the art are considered to be included in the invention. The description is merely examples of embodiments. It is understood that any other modifications, substitutions, and/or additions may be made, which are within the intended spirit and scope of the invention.

Throughout this specification and the claims which follow, unless the context requires otherwise, the word "comprise", and variations such as "comprises" and "comprising", will be understood to imply the inclusion of a stated integer or step or group of integers or steps but not the exclusion of any other integer or step or group of integers or steps.

The reference in this specification to any prior publication (or information derived from it), or to any matter which is known, is not, and should not be taken as an acknowledgment or admission or any form of suggestion that that prior publication (or information derived from it) or known matter forms part of the common general knowledge in the field of endeavour to which this specification relates.

2013222067 21 Jan 2016

THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:

1. A method of repairing a damaged section of a pipe, comprising:
providing a liner having an open first end and a substantially closed second end;
5 impregnating the liner with a material capable of curing and hardening;
inverting the liner into the pipe with an inversion head, wherein the first end of the liner is
attached to a portion of the inversion head;
inflating the liner using a source of pressurized fluid to create pressure within the liner
which presses the liner against the wall of the pipe;
10 inflating a plug at least partially within the inversion head to substantially close the open
end of the liner at the inversion head and maintain pressure within the liner;
wherein the liner is inverted through the inversion head prior to the inflation of the plug;
and
allowing the material to cure and harden.
15
2. The method of claim 1 wherein the liner comprises a first layer of felt and a second
layer comprising an impervious material.
3. The method of claim 1 or 2 wherein the liner is inverted from a position wherein
20 the layer of felt is on the inside to a position wherein the impervious layer is on the inside
as the liner is inverted through the inversion head.
4. The method of claim 3 wherein the layer of felt is positioned between the
impervious material and the pipe after the liner has been inverted into the pipe.

25

21 Jan 2016
2013222067

5. The method of any one of the preceding claims further comprising attaching a vacuum head to the inversion head to aid in impregnating the liner with the material capable of curing and hardening.

5 6. The method of claim 5 further comprising removing the vacuum head and attaching a fluid source to invert the liner into the pipe.

7. The method of claim 6 further comprising replacing the fluid source with a curing head to aid in curing the material.

10

8. The method of claim 7 further comprising providing steam to the lumen of the inflated liner to decrease curing time for the material.

15

9. The method of claim 8 wherein the vacuum head, fluid source, and curing head are selectively attached to an intake of the inversion head.

20

10. The method of any one of the preceding claims further comprising providing a bladder that is positionable from a configuration wherein the bladder is at the outside of the liner to a position wherein the bladder is at least partially at the interior of the liner within the pipe.

11. The method of claim 10 further comprising inflating the bladder to press the liner against the wall of the pipe.

2013222067 21 Jan 2016

12. An assembly for repairing a damaged section of a pipe, comprising:
an inversion head having an intake end and an opposite discharge end;
a liner having an open first end and a substantially closed second end, the first end attached
to the discharge end of the inversion head;
- 5 a plug positioned at least partially within the inversion head and configured to be inflated
to substantially close off the open first end of the liner;
- wherein the intake end of the inversion head configured to removably attach to an
inversion member for inflating the liner, and a curing head for curing a material
capable of curing and hardening that is impregnated in the liner; and
- 10 wherein the liner is inverted through the inversion head and the plug to be positioned
within the damaged section of pipe.
13. The assembly of claim 12 wherein the plug is an inflatable plug or a mechanical
plug.
- 15
14. The assembly of claim 12 or 13 further comprising a vacuum head, a fluid source,
or a curing head attached to the intake end of the inversion head.
15. The assembly of any one of claims 12 to 14 further comprising a bladder
20 operatively connected to the liner such that the bladder and liner are inverted from a
position wherein the liner is substantially within the bladder to a position wherein the liner
substantially surrounds the bladder.

2013222067 21 Jan 2016

16. The assembly of any one of claims 12 to 15 wherein the liner is impregnated with a material capable of curing and hardening.

17. The assembly of any one of claims 12 to 15 further comprising a curing head

5 operatively connected to the inversion head and comprising:

a substantially circular body having a first side and a second side;

an inflation port;

a curing port;

a substantially flexible tube, having a first end and a second end, slidably extending

10 through the curing port; and

a drainage port.

18. A method of repairing a damaged section of a pipe, comprising:

providing a liner having an open first end and a substantially closed second end;

15 attaching the open end of the liner to a discharge end of an inversion head;

impregnating the liner with a material capable of curing and hardening by applying

vacuum pressure at an intake end of the inversion head;

inverting the liner into the pipe by a fluid source attached to the intake end of the inversion

head;

20 inflating the liner using a source of pressurized fluid to create pressure within the liner

which presses the liner against the wall of the pipe;

inflating a plug at least partially within the inversion head to substantially close the open

end of the liner at the inversion head and maintain pressure within the liner;

2013222067 21 Jan 2016

wherein the liner is inverted through the inversion head prior to the inflation of the plug;
and
allowing the material to cure and harden.

5 19. The method of claim 18 further comprising curing the material impregnated in the
liner by attaching a curing head to the inversion head and inserting steam to the lumen of
the liner.

10 20. The method of claim 18 or 19 wherein the liner comprises a first layer of felt and a
second layer comprising an impervious material, and wherein the liner is inverted from a
position wherein the layer of felt is on the inside to a position wherein the impervious layer
is on the inside as the liner is inverted through the inversion head.

15 21. The method of claim 1 further comprising the step of removing the source of
pressurized fluid after the plug is inflated.

22. The method of claim 18 further comprising the step of removing the source of
pressurized fluid after the plug is inflated.

Fig. 1




Fig. 2




Fig. 3A





Fig. 3B






Fig. 4A





Fig. 4B

Fig. 5






Fig. 6A




Fig. 6B




Fig. 7