

ENVIRONMENTALLY-FRIENDLY VINYL HYBRID RESIN

HYBRID VINYL ESTER WITH HIGH-RIGID POLYMER BACKBONE

- ✓ **EXCELLENT CATALYZED STABILITY**
- ✓ **NO STYRENE, NO VOC'S**
- ✓ **HIGH TEMPERATURE PERFORMANCE**
- ✓ **RESISTANCE TO SAG AND DRAINING AROUND VERTICAL SURFACE AND REINFORCEMENT**

Typical Mechanical Properties

Test	Unit of Measure	Nominal	Test Method
Tensile Strength	psi	9,500	ASTM D 638
Tensile Modulus	kpsi	490	ASTM D 638
Tensile Elongation	%	2.3	ASTM D 638
Flexural Strength	psi	18,100	ASTM D 790
Flexural Modulus	kpsi	560	ASTM D 790
Heat Distortion Temp	°C/°F	150/302	ASTM D648
Specific Gravity	-	1.2	ASTM D 2583
Barcol Hardness Model 934-1	HB	46	ASTM D 2583



**TURN-KEY TRAILERS &
TURN-KEY BOX TRUCKS**



**ZERO DOWN, NO PAYMENTS
FOR 90-DAYS**

**ZERO DIG CIPP TRENCHLESS TECHNOLOGY
WWW.PERMA-LINER.COM**

**TO LEARN MORE CALL
1-866-336-2568**